

SPECIFICATIONS



eS_{pro} K1

eS_{pro} K2

**CHOOSE THE VEHICLE
BEST SUITED TO
YOUR BUSINESS.**



**Colours and graphics can be
customised to satisfy the specific
requirements of your business.**

Askoll
I am electric

www.askollelectric.com

	Traction	
	eSproK1	eSproK2
Motor	Askoll brushless permanent magnet electric motor	
Power	2.200 W *	
Max speed	45 km/h *	
Max torque	130 Nm (to the wheel)	
Regeneration	Yes	
Transmission	Pulley w/ toothed timing belt	

	Removable battery	
	eSproK1	eSproK2
Type	Lithium-ion	
Capacity (2 packs)	max. 2.820 Wh	
Voltage	54 V	
Weight (for each battery pack)	8 kg	
Charging time 2 batteries	7,5 hours (80%)	
Range (up to)	98 km *	

	General information	
	eSproK1	eSproK2
Front Lighting	Halogen	
Back Lighting	LED	
Direction indicator lighting	LED built into the body	
Colours available	White	
Customisations	Colours and graphics can be customised for specific requirements	

	Cycle parts	
	eSproK1	eSproK2
Front suspension	Hydraulic telescopic fork	
Back suspension	Hydraulic shock absorber	
Brakes	Front: hydraulic disk Ø 190 mm Back: drum Ø 140 mm	
Front tyre	80 / 80 - 16"	
Back tyre	90 / 80 - 16"	
Wheelbase	1.245 mm	
Seat height	760 mm	
Weight in running order	76 kg *	80 kg *
Max. weight (vehicle + driver + additional load)	235 kg	

	Other information	
	eSproK1	eSproK2
Approval category	L1	
Carrier baskets	Front: 57x38 cm (Max 20 kg)	Front: 57x38 cm (Max 20 kg) Back: 55,5x37,5 cm (Max 30 kg)

Technical specifications may be subject to change without prior notice.

* According 168 / 2013 CE